


CHAIN

NACM STANDARD CHAIN (S4) 316L STAINLESS STEEL



ITEM	SIZE	A	B	C	WLL	BL	WT
					(lb)	(lb)	(lb/ft)
S0602-0004	5/32"	0.16"	0.77"	0.28"	500	2,000	0.23
S0602-0005	3/16"	0.20"	0.92"	0.34"	930	3,720	0.32
S0602-0007	1/4"	0.25"	1.00"	0.43"	1,570	6,280	0.57
S0602-0008	5/16"	0.32"	1.03"	0.49"	2,400	9,600	0.92
S0602-0010	3/8"	0.39"	1.22"	0.61"	3,550	14,200	1.50
S0602-0012	1/2" (7/16)	0.47"	1.50"	0.78"	5,400	21,600	2.00
S0602-0016	5/8"	0.63"	1.91"	0.90"	9,800	39,200	3.31
S0602-0020	3/4"	0.75"	2.75"	1.17"	15,000	60,000	5.00
S0602-0025	1"	1.00"	3.53"	1.61"	23,250	73,000	9.00


NOTE:
MOST ECONOMIC AND COMMONLY USED CHAIN FOR INDUSTRIAL AND MARINE APPLICATIONS. THIS CHAIN COMPLIES FULLY WITH ALL REQUIREMENTS OF THE U.S. NATIONAL ASSOCIATION OF CHAIN MANUFACTURERS' (NACM'S) SPECIFICATIONS.

GRADE S4

S0604-0007	9/32"	0.28"	0.84"	0.40"	2,000	8,000	0.39
S0604-0008	5/16"	0.32"	1.03"	0.49"	2,400	9,600	0.92
S0604-0010	3/8"	0.39"	1.33"	0.57"	3,550	14,200	1.60
S0604-0013	1/2"	0.51"	1.59"	0.76"	6,500	26,000	2.10

NOTE:
GRADE S4 CHAIN IS MADE TO "G4" DIMENSIONS. IT FITS MANY STANDARD U.S. WINDLASSES AND INDUSTRIAL APPLICATIONS. THIS CHAIN COMPLIES FULLY WITH ALL REQUIREMENTS OF THE U.S. NATIONAL ASSOCIATION OF CHAIN MANUFACTURERS' (NACM'S) SPECIFICATIONS.

LIFTING CHAIN (S5) 316L STAINLESS STEEL




ITEM	SIZE	A	B	C	WLL	BL	WT
					(lb)	(lb)	(lb/ft)
S0603-0005	3/16"	0.19"	0.58"	0.25"	1,100	4,400	0.36
S0603-0007	9/32"	0.28"	0.85"	0.38"	2,200	8,800	0.97
S0603-0008	5/16"	0.32"	0.95"	0.45"	2,700	10,800	0.98
S0603-0010	3/8"	0.39"	1.18"	0.55"	4,400	17,600	1.41
S0603-0013	1/2"	0.51"	1.55"	0.75"	7,300	29,200	2.60

RATED FOR OVERHEAD LIFTING

NOTE:
CALIBRATED GRADE 50 LIFTING CHAIN, MADE TO GRADE 80 DIMENSIONS. NEVER EXCEED WORKING LOAD LIMIT. WORKING LOADS ARE BASED ON GRADUAL PULL AND NOT SHOCK LOADS. MAKE SURE THAT ALL COMPONENTS IN YOUR ASSEMBLY ARE OVERHEAD LIFTING RATED AND HAVE THE SAME WORKING LOADS.


ANCHOR CHAIN (S1) 316L STAINLESS STEEL



ITEM	SIZE	A	B	C	WLL	BL	WT
					(lb)	(lb)	(lb/ft)
S0601-0007	1/4"	0.28"	0.87"	0.36"	2,000	8,000	0.76
S0601-0008	5/16"	0.32"	0.95"	0.41"	2,400	9,600	0.94
S0601-0010	3/8"	0.39"	1.10"	0.54"	3,750	15,000	1.60
S0601-0013	1/2"	0.51"	1.38"	0.74"	6,500	26,000	2.74

NOTE:
**THIS CALIBRATED CHAIN HAS DIMENSIONS OF "BBB" CHAIN AND FITS MANY STANDARD WINDLASSES. ALSO SEE THE S0604 SERIES FOR OTHER WINDLASS CHAIN.
 THIS CHAIN COMPLIES WITH ALL REQUIREMENTS OF DIN 766.**

LONG LINK CHAIN (S6) 304L STAINLESS STEEL



ITEM	SIZE	A	B	C	WLL	BL	WT
					(lb)	(lb)	(lb/ft)
S0606-0001	5/64"	0.08"	0.48"	0.14"	180	720	0.06
S0606-0002	3/32-7/64"	0.10"	0.69"	0.16"	300	1,200	0.10
S0606-0003	1/8"	0.12"	1.03"	0.20"	380	1,520	0.11
S0606-0004	5/32"	0.15"	1.26"	0.35"	500	2,000	0.18
S0606-0005	3/16"	0.20"	1.42"	0.39"	900	3,600	0.28
S0606-0006	1/4"	0.24"	1.62"	0.47"	1,200	4,800	0.42


NOTE:
**LONG LINK CHAIN IS THE LEAST EXPENSIVE STAINLESS STEEL CHAIN. THE LINKS ON AVERAGE ARE 1.5 TIMES LONGER THAN STANDARD CHAIN LINKS.
 THIS CHAIN COMPLIES WITH ALL REQUIREMENTS OF DIN 5685-C.**

Key:

Made in USA	Drop Forged	Precision Machined	Wire Formed
Import	Precision Cast	Stamped	Load Rated
			New Product

SPECIAL CHAIN (S2)

304L, 316L, ALUMINUM OR TITANIUM




ITEM	SIZE	A	B	C	WLL	WT
					(lb)	(lb/ft)
S0607-0002	5/64"	0.08"	0.87"	0.16"	55	0.04
S0607-0003	7/64"	0.12"	1.02"	0.23"	132	0.10
S0607-0004	1/8"	0.16"	0.94"	0.26"	410	0.20
S0607-0005	3/16"	0.20"	0.95"	0.38"	1,200	0.30
S0607-0007	9/32"	0.28"	0.87"	0.43"	2,000	0.93
S0607-0008	5/16"	0.32"	0.94"	0.46"	2,400	0.98
S0607-0010	3/8"	0.39"	1.10"	0.55"	3,550	1.38
S0607-0013	1/2"	0.51"	1.54"	0.69"	6,500	2.65

NOTE:

ALSO AVAILABLE IN 304L AS S0608 SERIES FOR BULK ORDERS. ALUMINUM OR TITANIUM CHAIN AVAILABLE ON SPECIAL ORDER.

TWIST LINK CHAIN (S8)

304 STAINLESS STEEL




ITEM	SIZE	A	B	C	WLL	WT
					(lb)	(lb/ft)
S0611-0001	5/64"	0.07"	0.30"	0.13"	150	0.07
S0611-0002	3/32 - 7/64"	0.09"	0.31"	0.16"	190	0.09
S0611-0003	1/8"	0.11"	0.48"	0.20"	280	0.13

NOTE:

IDEAL FOR DECORATIVE APPLICATIONS, SWINGS, ANIMAL CONTROL, WALLETS AND ACCESSORIES.

SINGLE JACK CHAIN (S9)

304/302 STAINLESS STEEL



ITEM	SIZE	A	B	C	WLL	BL	WT	
					(lb)	(lb)	(lb./100')	
S0621-0000	#18	1.2 MM	0.05"	0.39"	0.12"	5	20	1.85
S0621-0001	#16	1.6 MM	0.06"	0.52"	0.15"	10	40	3.00
S0621-0002	#14	2.0 MM	0.08"	0.63"	0.20"	16	65	5.00
S0621-0003	#12	2.5 MM	0.10"	0.75"	0.23"	29	115	8.50
S0621-0004	#10	3.3 MM	0.13"	0.85"	0.31"	43	170	14.70


NOTE:

I/A/W ASTM A466 AND NACM STANDARDS. SOLD IN 100 FOOT LENGTHS ONLY. U.S. STANDARD CHAIN. IDEAL FOR LIGHTING FIXTURES AND NOVELTIES.



DOUBLE LOOP CHAIN (S7)

304 STAINLESS STEEL



ITEM	SIZE	A	B	C	WLL	BL	WT
					(lb)	(lb)	(lb./100')
S0626-0003	#3	0.08"	1.14"	0.25"	90	360	6.1
S0626-0003	#1	0.11"	1.71"	0.35"	155	620	10.0
S0626-0003	2/0	0.14"	1.82"	0.37"	255	1,020	17.0


NOTE:

I/A/W ASTM A466 AND NACM STANDARDS. SOLD IN 100 FOOT LENGTHS ONLY. IDEAL FOR SWINGS, DECORATING APPLICATIONS AND NOVELTIES. OTHER SIZES AVAILABLE IN BULK ON SPECIAL ORDER.



SASH CHAIN (S10)

302 STAINLESS STEEL



ITEM	SIZE	A	B	C	D	WLL	WT	
						(lb)	(lb./100')	
S0631-0001	#35	0.9 MM	0.035"	0.08"	0.17"	0.57"	225	7
S0631-0002	#25	1.1 MM	0.042"	0.06"	0.24"	0.57"	200	5
S0631-0003	#8	0.6 MM	0.035"	0.06"	0.24"	0.57"	150	4

NOTE:

I/A/W ASTM A466 AND NACM STANDARDS. SOLD IN 100 FOOT LENGTHS ONLY. WT/lhd. = WEIGHT PER HUNDRED FEET. IDEAL FOR SMOOTH OPERATIONS OVER PULLEYS, LIGHTING FIXTURES AND NOVELTIES.




TRAILER SAFETY CHAIN PACK 316L STAINLESS STEEL



ITEM	A (size)	B (length)	C (end link)	WLL (lb)	WT (lb)
S0275-0001	1/4"	24"	5/16"	1,600	1.35
S0275-0002	5/16"	24"	3/8"	2,400	2.20

NOTE:
FOR ADDITIONAL SAFETY, THIS KIT CONTAINS ONE HIGH QUALITY QUICK LINK, PERMANENTLY MARKED WITH WLL, LOGO, SS316. CHAIN IS U.S. PRODUCED STAINLESS STEEL CHAIN, SHOWN ON PAGE 10 AS #S0602.



MARINE CHAIN PRE-PACK 316L STAINLESS STEEL



ITEM	SIZE	LENGTH	WLL (lb)	WT (lb)
C0132-0407	1/4"	4 FT.	1,570	3.00
C0132-0507	1/4"	5 FT.	1,570	3.60
C0132-0508	5/16"	5 FT.	2,400	4.70
C0132-0608	5/16"	6 FT.	2,400	5.20
C0132-0610	3/8"	6 FT.	3,750	9.00

NOTE:
PRE-CUT CHAIN IN BAR CODED PACKAGING. COMMONLY USED AS LEAD CHAIN FOR PLEASURE MARINE ANCHORS (GROUND TACKLE).


INDUSTRIAL CHAIN MINI-BARREL 316L STAINLESS STEEL



ITEM	SIZE	LENGTH	WLL (lb)	WT (lb)
S0132-04150	5/32"	150 FT.	500	35.00
S0132-05150	3/16"	150 FT.	930	48.00
S0132-07100	1/4"	100 FT.	1,570	57.00
S0132-08100	5/16"	100 FT.	2,400	92.00
S0132-10050	3/8"	50 FT.	3,550	75.00

NOTE:
THIS IS S0602 CHAIN. DIMENSIONS AND SPECS ON S0602 ARE SHOWN ON PAGE 10. IT IS THE MOST ECONOMIC AND COMMONLY USED CHAIN FOR INDUSTRIAL AND MARINE APPLICATIONS. AVAILABLE IN A MINI BARREL, IT IS IDEAL FOR STORE DISPLAYS.

SLING IDENTIFICATION TAG 304 STAINLESS STEEL



ITEM	A	B	C	WT (lb)
S0600-0001	0.09"	3.50"	1.50"	0.10

NOTE:
THIS TAG IS USED TO PERMANENTLY MARK SLINGS FOR OVERHEAD LIFTING AND SHOW MAXIMUM WORKING LOADS AT DIFFERENT ANGLES. SOLD WITH STAINLESS STEEL RING FOR EASY ATTACHMENT.

The Effect of Temperature on the Working Load Limit of Chain

Temperature		Reduction of Working Load Limit WHILE AT Temperature	Reduction of Working Load Limit AFTER EXPOSURE to Temperature
Fahrenheit	Celsius		
Below 400°F	Below 204°C	None	None
400°-800°F	204°-426°C	0-10%	None
801°-1000°F	427°-537°C	20%	None
1001°-1200°F	538°-649°C	30%	None
1201°-1300°F	650°-704°C	40%	None
1301°-1400°F	705°-760°C	50%	None
1401°-1500°F	761°-815°C	60%	None
1501°-1600°F	816°-871°C	75%	None

Key:

- Made in USA
- Drop Forged
- Precision Machined
- Wire Formed
- Import
- Precision Cast
- Stamped
- Load Rated
- New Product